AK60A

75 Watts

AK60A-75 Economy Series

Total Power	*75 Watts*
Input Voltages	*24V*
# of Outputs	*Single*

AK60A Technical Manual - Click Here

SPECIAL FEATURES

- High efficiency - up to 88%
- 500 KHz fixed frequency
- 85°C Baseplate operating temperature (with no derating)
- Low output ripple and noise
- Excellent transient response
- High reliability - over 1 million hours MTBF
- Wide input voltage range
- TTL compatible enable control
- Adjustable output voltage
- Overtemperature and short circuit protection

ENVIRONMENTAL

Operating temperature (baseplate): -20°C to +85°C

Storage temperature: -40°C to +105°C

Overtemperature protection: 90°C typical

MTBF: > 1 million hours (50°C baseplate)

SAFETY

UL	UL 1950	E182206
CSA	CSA22.2-234 CSA22.2-950	LR53982C
VDE	IEC950	
EN	60950	
CE	CE Mark (LVD)	

ELECTRICAL SPECIFICATIONS

Input

Input Range ..... 18 to 36 VDC

Efficiency ..... 82% typical (5V @ 15A)
88% typical (12V @ 6.3A)

Control

Voltage Adjust ..... 90 to 110% Vo

Enable ..... TTL compatible (low to enable)

PRI Aux ..... Use with large load capacitance

Output

Load Regulation ..... 0.3% typical down to 10% load

Line Regulation ..... 0.1% typical

Noise/Ripple ..... 100 mV typical (output below 5V)
2% typical (output 5V and over)

Remote sense ..... Up to 0.5V

Output Voltage Adjust Range ..... ±10% of nominal output

Transient Response ..... 10% max deviation with 500µs (25-75% full load) recovery

Overvoltage Protection ..... 130% nominal Vo

Current Limit ..... 115% Io max

NOTES

Nominal values apply with sense pins connected and other control pins unconnected.

Specifications subject to change without notice.

ASIA
6F., CDW Building
382-392 Castle Peak Road
Tsuen Wan, N.T., Hong Kong
Telephone: 852-2437-9662
Facsimile: 852-2402-4426

EUROPE
Astec House, Waterfront Business Park
Merry Hill, Dudley
West Midlands, DY5 1LX, UK
Telephone:+44(0)1384-842211
Facsimile:+44(0)1384-843355

AMERICAS
5810 Van Allen Way
Carlsbad, CA 92008
Telephone: 760-930-4600
Facsimile: 760-930-0698

ORDERING INFORMATION

Input Voltage	Output Voltage	Output Current	Model Number
24V	5V	15A	AK60A-024L-050F15
24V	12V	6.3A	AK60A-024L-120F06
24V	15V	5A	AK60A-024L-150F05
24V	24V	3A	AK60A-024L-240F03

Please contact Astec for information on other output voltages, power ranges and configurations.

DIMENSIONS



**Must be connected to protective earth*



Viewed from pins side. Dimensions in mm (inches)

PIN ASSIGNMENTS

Input	Output		Control Pins	
31. +ve	22.	+ve	1. +SENSE	Secondary side controls
32. –ve	23.		2. RSV	
	24.		3. V ADJ	
	26.	–ve	4. -SENSE	
	27.		5. S COM	Primary side controls
	28.		6. PRI-AUX	
			7. ENABLE	
			8. CLK-IN	

CONNECTIONS